



LSR MINI

- As the name suggests, extremely small, exquisite, and extremely valuable
- This type of equipment is suitable for small volume production
 - Laboratory
- Project early development
- Easy to operate

LSR MINI



DESCRIPTION

- Pneumatic driving of 1liter raw material cylinder and emptying signal
- Pneumatic driving metering unit
- Accurate and pulse-free metering, suitable for small amount of product
- The maximum single injection amount is 20 cubic centimeters
- Fixed mixing ratio 1:1
- Easy to operate
- Customizable for individual formulations



TECHNICAL DATA

Viscosity	< 1,000,000 mPas
Output mixed material	Max. 20 cm ³ (depending on viscosity)
Mixing ratio	1:1
Color metering	0.3% ~ 4%
Actuation	Pneumatic
Electric data	200-480 VAC ,50/60Hz,1P,+N.+PE
Connection LIM machine	24 VDC
Pneumatic system	R1/4", 6 bar
Weight	< 80kg



2KM MUCOMAC Multi component special machinery (Guangzhou) Co., Ltd
Add: No. Sheng Li Industrial Park North of Chao tian industrial zone shi Lian Lu
Shi Lou Town Panyu Distri Guangzhou P.R.C Postcode: 511447

Tel: +8620 - 34852366 / 2866
Fax: +8620 - 34852966 / 2566
Email: info@2kmmucomac.com

www.2kmmucomac.com
www.mucomac.com
Service hotline
400-900-3889